

ViewStation Group Conferencing Products

| System Type | Product Placement | Differentiating Features | Max Data Rate H.320 | Max Data Rate H.323 | Network Interface | Options Available | Monitor Support | Multipoint Capability |
|--------------------------|--|---|----------------------|---------------------|--|---|-----------------|--|
| ViewStation SP128 | Small room system 1-3 people | Document camera or VCR playback Microphone head set (optional) 1 LAN port Includes 1 mic pod | 128 Kbps | 768 Kbps | ISDN, Ethernet/LAN | N/A | 1 | N/A |
| ViewStation SP384 | Small room system 1-3 people | Document camera or VCR playback Microphone head set (optional) 1 LAN port Includes 1 mic pod | 384 Kbps | 768 Kbps | ISDN, Ethernet/LAN | N/A | 1 | N/A |
| ViewStation 128 | Medium or large room system 1-10 people | Document camera & VCR playback 2nd mic pod (optional) 2-port LAN hub * Streaming supported | 128 Kbps | 768 Kbps | ISDN, Ethernet/LAN | ** Quad BRI Module ** MP Upgrade Kit (Requires hardware exchange) | 2 | Quad BRI Module and software upgrade required for MP |
| ViewStation H.323 | Medium or large room system 1-10 people | Document camera & VCR 2nd mic pod (optional) 2-port LAN hub * Streaming supported | Optional | 768 Kbps | Ethernet/LAN | Quad BRI Module DCP Module V.35 Module MP Upgrade Kit | 2 | Quad BRI Module and software upgrade required for MP |
| | | Optional Quad BRI Module | 512 Kbps | 768 Kbps | ISDN, Ethernet/LAN | | | |
| | | Optional DCP Module | 512 Kbps | 768 Kbps | Lucent Definity ECS Ethernet/LAN | | | |
| | | Optional V.35 Module | 768 Kbps | 768 Kbps | V.35/RS-449 Ethernet/LAN T1/E1, ATM, VPN | | | |
| ViewStation MP | Medium or large room system 1-10 people | On-demand multipoint capability Document camera & VCR 2nd mic pod (optional) * Streaming supported | 512 Kbps | 768 Kbps | ISDN, Ethernet/LAN | N/A | 2 | 4 @ 128 Kbps 3 @ 256 Kbps ISDN |
| ViewStation FX | Boardroom, classroom or custom room system 1-30+ people | TV-quality video Supports 2nd PTZ camera RS 232 dataport SXGA resolution graphics support Built-in multipoint up to 4 @ 384 Built-in streaming capabilities International POTS add-in Dual microphones standard | Optional | 2 Mbps | Ethernet/LAN | Quad BRI Module PRI Module V.35 Module | 2+ (1 XGA) | 4 @ 384 Kbps 3 @ 512 Kbps via ISDN or LAN |
| | | Optional Quad BRI Module | 512 Kbps | 2 Mbps | ISDN, Ethernet/LAN | | | |
| | | Optional PRI Module | 1.472 T1 1.922 E1 | 2 Mbps | ISDN, Ethernet/LAN | | | |
| | | Optional V.35 Module | 1.472 T1 1.922 E1 | 2 Mbps | V.35/RS-449 T1/E1, ATM, VPN Ethernet/LAN | | | |
| VS4000 Codec | Custom room system 1-30+ people | TV-quality video Supports 2 external cameras RS 232 dataport SXGA resolution graphics support Built-in multipoint up to 4 @ 384 Built-in streaming capabilities On/off echo cancellor International POTS add-in Dual microphones standard | Optional | 2 Mbps | Ethernet/LAN | Quad BRI Module PRI Module V.35 Module | 2+ (1 XGA) | 4 @ 384 Kbps 3 @ 512 Kbps via ISDN or LAN |
| | | Optional Quad BRI Module | 512 Kbps | 2 Mbps | ISDN, Ethernet/LAN | | | |
| | | Optional PRI Module | 1.472 T1 1.922 E1 | 2 Mbps | ISDN, Ethernet/LAN | | | |
| | | Optional V.35 Module | 1.472 T1 1.922 E1 | 2 Mbps | V.35/RS-449 T1/E1, ATM, VPN Ethernet/LAN | | | |

*with optional Polycom StreamStation

**Not Available in Asia or ROW

